

## SB 18 LTX BL Q I (602361660) Cordless hammer drill

Order No. 602361660  
EAN 4061792187832



Representative picture



- A true power house: safe, brushless cordless hammer drill with maximum power for the toughest applications
- Hammer drill function for drilling in masonry
- Metabo quick system: quick exchange of chucks, bit holders, angle adapters and more for flexible work
- Selectable &#34;impuls&#34; mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Robust, durable gear housing made from aluminium die-cast
- Spindle with magnetic hexagon recess for screwdriver bits for working without chuck
- Powerful Brushless motor for greatest efficiency and long battery pack runtime
- Precision Stop: electronic torque control with increased precision for precise, delicate working
- Overload protection: protects the motor from overheating
- Euro collar (Ø 43 mm) for versatile use
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly - for high user safety
- Integrated LED work light with afterglow function for optimal brightness in the work area
- With handy belt hook and bit case which can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

### Technical values

#### KEY FIGURES

Type of battery pack	LiHD
Battery voltage	18 V

Battery pack capacity	2 x 5.5 Ah
Maximum torque, soft	65 Nm / 575 in-lbs
Pulse torque	65 Nm / 575 in-lbs
Maximum torque, hard	130 Nm / 1151 in-lbs
Adjustable torque	1 - 20 Nm // 9 - 177 in-lbs
Drill-Ø masonry	16 mm / 5/8 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	68 mm / 2.68 "
No-load speed	0 - 550 / 0 - 2000 rpm
Maximum impact rate	38000 bpm
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Collar diameter	43 mm / 1 11/16 "
Weight without battery pack	1.8 kg / 4 lbs
Weight with battery pack	2.8 kg / 6.2 lbs

## VIBRATION

Drilling in metal	2.6 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Impact drilling concrete	16.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.7 m/s <sup>2</sup>

## NOISE EMISSION

Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

- Quick-change chuck
- Side handle
- Belt hook and bit case
- 2 LiHD battery packs (18 V/5.5 Ah)
- Quick charger ASC 145 "AIR COOLED"

- metaBOX 145 L