

# SB 18 L Set (614053710) Cordless hammer drill

Order No. 614053710 EAN 4061792252226



Representative picture





- Reliable, powerful hammer drill for all standard drilling and screwdriving applications
- Hammer drill function for drilling in masonry
- Mobile workshop (78 pieces): 5 wood drill bits (4/5/6/8/10mm), 5 masonry drill bits (5/6/7/8/10mm), 14 HSS drill bits (1.5/1.5/2/2/2.5/3/3/3.5/4/4.5/5/5.5/6/6.5mm), 20 screwdriver bits length 25mm (PH1/PH2/PH3/PZ1/PZ2/PZ2/PZ2/PZ3/H3/H4/H5/H6/T15/T20/T25/T30/S4/S5/S6), 10

(PH1/PH2/PH3/PZ1/PZ2/PZ2/PZ2/PZ3/H3/H4/H5/H6/T15/T20/T25/T30/S4/S5/S6), 10 screwdriver bits length 50mm (S4/S5/S6/PZ1/PZ2/PZ3/T15/T20/T25/T30), 10 screwdriver bits length 75mm (S4/S5/S6/PZ1/PZ2/PZ3/T15/T20/T25/T30), bit holder (60mm), 8 socket wrench (6/7/8/9/10/11/12/13mm), countersink (12.7mm), centering pin (5×100mm), cutter knife with 2 spare blades, measuring tape (3m/10"), pencil (HB)

- Overload protection: protects the motor from overheating
- Integrated LED work light with afterglow function for optimal brightness in the work area
- · With handy belt hook and bit case which can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

### Technical values

#### **KEY FIGURES**

Type of battery pack	LiPOWER
Battery voltage	18 V
Battery pack capacity	2 x 2 Ah

Maximum torque, soft	26 Nm / 230 in-lbs
Maximum torque, hard	60 Nm / 531 in-lbs
Adjustable torque	0.7 - 5.5 Nm // 6.2 - 48.7 in-lbs
Drill-Ø masonry	13 mm / 1/2 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	36 mm / 1 13/32 "
No-load speed	0 - 450 / 0 - 1850 rpm
Maximum impact rate	28500 bpm
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Weight without battery pack	1.2 kg / 2.6 lbs
Weight with battery pack	1.6 kg / 3.5 lbs

## **VIBRATION**

Drilling in metal	$1.7 \text{ m/s}^2$
Uncertainty of measurement K	$1.5 \text{ m/s}^2$
Impact drilling concrete	$11.8 \text{ m/s}^2$
Uncertainty of measurement K	$1.5 \text{ m/s}^2$
Screwdriving without impact	$0.5 \text{ m/s}^2$
Uncertainty of measurement K	$1.5 \text{ m/s}^2$

### **NOISE EMISSION**

Sound pressure level	91 dB(A)
Sound power level (LwA)	99 dB(A)
Uncertainty of measurement K	5 dB(A)

# Scope of delivery

- Keyless chuck
- Belt hook and bit case
- 2 LiPOWER Battery Packs (18 V/2.0 Ah)
- Charger SC 36
- Plastic carry case
- Accessory set