

SB 18 Set (602245710) Cordless hammer drill

Order No. 602245710
EAN 4061792249509



Representative picture



- Practical, lightweight everyday option for drilling and screw fitting.
- Hammer drill function for drilling in masonry
- Mobile workshop (78 pieces): 5 wood drill bits (4/5/6/8/10mm), 5 masonry drill bits (5/6/7/8/10mm), 14 HSS drill bits (1.5/1.5/2/2/2.5/3/3/3.5/4/4.5/5/5.5/6/6.5mm), 20 screwdriver bits length 25mm (PH1/PH2/PH2/PH3/PZ1/PZ2/PZ2/PZ2/PZ3/H3/H4/H5/H6/T15/T20/T25/T30/S4/S5/S6), 10 screwdriver bits length 50mm (S4/S5/S6/PZ1/PZ2/PZ3/T15/T20/T25/T30), 10 screwdriver bits length 75mm (S4/S5/S6/PZ1/PZ2/PZ3/T15/T20/T25/T30), bit holder (60mm), 8 socket wrench (6/7/8/9/10/11/12/13mm), countersink (12.7mm), centering pin (5×100mm), cutter knife with 2 spare blades, measuring tape (3m/10"), pencil (HB)
- Integrated working light to illuminate the contact area
- With handy belt hook and bit case which can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical values

KEY FIGURES

| | |
|-----------------------|--------------------|
| Type of battery pack | LiPOWER |
| Battery voltage | 18 V |
| Battery pack capacity | 2 x 2 Ah |
| Maximum torque, soft | 24 Nm / 212 in-lbs |

| | |
|-----------------------------|-------------------------------|
| Maximum torque, hard | 48 Nm / 425 in-lbs |
| Adjustable torque | 0.5 - 4.5 Nm // 4 - 40 in-lbs |
| Drill-Ø masonry | 10 mm / 3/8 " |
| Drill Ø steel | 10 mm / 3/8 " |
| Drill-Ø soft wood | 20 mm / 3/4 " |
| No-load speed | 0 - 450 / 0 - 1600 rpm |
| Maximum impact rate | 24000 bpm |
| Chuck capacity | 1 - 10 mm // 1/32 - 3/8 " |
| Weight without battery pack | 0.92 kg / 2 lbs |
| Weight with battery pack | 1.3 kg / 2.9 lbs |

VIBRATION

| | |
|------------------------------|----------------------|
| Drilling in metal | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Impact drilling concrete | 23 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

NOISE EMISSION

| | |
|------------------------------|----------|
| Sound pressure level | 86 dB(A) |
| Sound power level (LwA) | 97 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

- Keyless chuck
- Belt hook and bit case
- 2 LiPOWER Battery Packs (18 V/2.0 Ah)
- Charger SC 36
- Plastic carry case
- Accessory set