metabo

BS 18 LTX BL Q I (602359850) Cordless drill / screwdriver

Order No. 602359850 EAN 4061792188211



Representative picture















- A true power house: safe, brushless drill with maximum power for the toughest applications
- Metabo quick system: quick exchange of chucks, bit holders, angle adapters and more for flexible work
- Selectable " impuls " mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- · Spindle with magnetic hexagon recess for screwdriver bits for working without chuck
- Precision Stop: electronic torque control with increased precision for accurate and intricate working
- · Variable speed, forward and reverse rotation and quick stop for versatile use in wood and metal
- Overload protection: protects the motor from overheating
- Euro collar (Ø 43 mm) for versatile use
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly for high user safety
- · Integrated LED work light with afterglow function for optimal brightness in the work area
- · With handy belt hook and bit case which can be fixed either on the right or left side
- · Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical values

KEY FIGURES

| Maximum torque, soft | 65 Nm / 575 ft. lbs |
|----------------------|-----------------------------|
| Pulse torque | 65 Nm / 575 in-lbs |
| Maximum torque, hard | 130 Nm / 1151 ft. lbs |
| Adjustable torque | 1 - 20 Nm // 9 - 177 in-lbs |

| Drill Ø steel | 13 mm / 1/2 " |
|-----------------------------|-----------------------------|
| Drill-Ø soft wood | 68 mm / 2.68 " |
| No-load speeds | 0 - 550 / 0 - 2000 rpm |
| Chuck capacity | 1.5 - 13 mm // 1/16 - 1/2 " |
| Collar diameter | 43 mm / 1 11/16 " |
| Weight without battery pack | 1.7 kg / 3.7 lbs |
| Weight with battery pack | 2.1 kg / 4.6 lbs |

VIBRATION

| Drilling in metal | 2.2 m/s^2 |
|------------------------------|---------------------|
| Uncertainty of measurement K | 1.5 m/s^2 |

NOISE EMISSION

| Sound pressure level | 76 dB(A) |
|------------------------------|----------|
| Sound power level (LwA) | 87 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

- Quick-change chuck Quick-change bit holder
- Side handle
- Belt hook and bit case
- without battery pack, without charger