

WB 18 LTX BL 15-125 Quick (601730660) Cordless angle grinder

Order No. 601730660
EAN 4061792229051



Representative picture



- Brushless cordless angle grinder of the new generation: the most powerful one in its class, as powerful as a 1,500 Watt mains-powered tool
- Service-free Brushless motor with highest efficiency and maximum handiness
- Fast brake system for highest user safety: Disc stops within 1.5 seconds after switching off
- M-Quick System for tool-free disc change at the touch of a button
- Tool-free adjustable guard; twist-proof
- Battery pack can be rotated in 90° steps for best ergonomics in any working position
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety
- Electronic overload protection, soft start and restart protection
- Detachable dust protection filter protects motor from coarse particles
- With metaBOX, the intelligent solution for transport and storage
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical values

KEY FIGURES

| | |
|-----------------------|------------|
| Type of battery pack | LiHD |
| Battery pack capacity | 2 x 5.5 Ah |
| Battery voltage | 18 V |

| | |
|-----------------------------|-----------------|
| Disc-Ø | 125 mm / 5 " |
| Max. cutting depth | 33 mm / 1.299 " |
| No-load speed | 10000 rpm |
| Spindle thread | M 14 |
| Handle circumference | 159 |
| Weight without battery pack | 2 kg |
| Weight with battery pack | 3 kg |

VIBRATION

| | |
|------------------------------|----------------------|
| Surface grinding | 7.1 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 1.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

NOISE EMISSION

| | |
|------------------------------|----------|
| Sound pressure level | 85 dB(A) |
| Sound power level (LwA) | 96 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

- Guard
- Inner support flange
- M-Quick flange nut
- Metabo VibraTech (MVT) side handle
- Dust Protection Filter
- 2 LiHD battery packs (18 V/5.5 Ah)
- Quick charger ASC 145 "AIR COOLED"
- metaBOX 165 L