

# SBE 650 Impuls (600743500) Schlagbohrmaschine

Order No. 600743500  
EAN 4061792201613



Representative picture



- Handliche, leichte Schlagbohrmaschine mit variabler Drehzahl für viele Bohr- und Schaubarbeiten
- Vario (V)-Elektronik zum Arbeiten mit materialgerechten Drehzahlen
- Stellrad zur Vorwahl der Drehzahl
- Zuschaltbarer Impulsbetrieb zum Herausdrehen festsitzender Schrauben und Anbohren auf glatten Oberflächen
- Rechts-Linkslauf
- Spindel mit Innensechskant für Schrauber-Bits zum Arbeiten ohne Bohrfutter

## Technical values

### KENNWERTE

|                     |                    |
|---------------------|--------------------|
| Output power        | 320 W              |
| Maximum torque      | 10 Nm // 88 in-lbs |
| Drill-Ø masonry     | 16 mm / 5/8 "      |
| Drill-Ø concrete    | 14 mm / 9/16 "     |
| Drill Ø steel       | 13 mm // 1/2 "     |
| Drill-Ø soft wood   | 30 mm // 1 3/16 "  |
| Speed at rated load | 1500 rpm           |

|                                     |                             |
|-------------------------------------|-----------------------------|
| Maximum impact rate                 | 44800 bpm                   |
| Gears                               | 1                           |
| Chuck capacity                      | 1.5 - 13 mm // 1/16 - 1/2 " |
| Collar diameter                     | 43 mm / 1 11/16 "           |
| Drill spindle with hexagonal recess | 6.35 mm / 1/4 "             |
| Drill spindle thread                | 1/2 " - 20 UNF              |
| Chuck clamping type                 | Keyless chuck               |
| Weight (without power cable)        | 1.8 kg                      |
| Cable length                        | 2.5 m / 8 ft m              |

## VIBRATION

|                              |                       |
|------------------------------|-----------------------|
| Drilling in metal            | 5.8 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |
| Impact drilling concrete     | 24.4 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |

## GERÄUSCHEMISSION

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 91 dB(A)  |
| Sound power level (LwA)      | 102 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

- Futuro Plus keyless chuck
- Side handle
- Drilling depth guide
- Plastic carry case