metabo

# WEP 17-150 Quick (600507000) Angle grinder

Order No. 600507000 EAN 4061792179820



Representative picture

















- Maximum productivity: 1,700 Watt angle grinder with the power of a large grinder and the compactness of a small one for quickest material removal on industrial applications
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Paddle switch with dead man function: safe to operate due to an ergonomically integrated non-slip switch
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cuttina
- Auto-stop carbon brushes to protect the motor

### Technical values

#### **KEY FIGURES**

Disc-Ø 150 mm // 6 "

Rated input power 1700 W

| No-load speed                | 9600 rpm           |
|------------------------------|--------------------|
| Speed at rated load          | 9600 rpm           |
| Torque                       | 4.3 Nm / 38 in-lbs |
| Spindle thread               | M 14               |
| Handle circumference         | 197 mm / 7 3/4 "   |
| Weight (without power cable) | 2.6 kg / 5.7 lbs   |
| Cable length                 | 4 m / 13 ft        |

## **VIBRATION**

| Surface grinding             | $6.8 \text{ m/s}^2$ |
|------------------------------|---------------------|
| Uncertainty of measurement K | $1.5 \text{ m/s}^2$ |
| Grinding with sandpaper      | $3 \text{ m/s}^2$   |
| Uncertainty of measurement K | $1.5 \text{ m/s}^2$ |

### **NOISE EMISSION**

| Sound pressure level         | 93 dB(A)  |
|------------------------------|-----------|
| Sound power level (LwA)      | 104 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

# Scope of delivery

- Guard
- Inner support flange
- M-Quick flange nut
- Metabo VibraTech (MVT) side handle