metabo

# WEV 17-125 Quick (600516000) Angle grinder

Order No. 600516000 EAN 4007430306593



#### Representative picture















- Maximum productivity: 1,700 Watt angle grinder with the power of a large grinder and the compactness of a small one for quickest material removal on industrial applications
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- · Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- · Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Electronic overload protection for long service life
- · Electronic soft start for smooth start-up
- Restart protection after power interruption
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cuttina
- · Auto-stop carbon brushes to protect the motor

### Technical values

#### **KEY FIGURES**

Disc-Ø 125 mm // 5 "

Rated input power 1700 W

Output power	1040 W
No-load speed	2800 - 11000 rpm
Speed at rated load	11000 rpm
Torque	3.7 Nm / 33 in-lbs
Spindle thread	M 14
Handle circumference	206 mm / 8 1/8 "
Weight (without power cable)	2.5 kg / 5.5 lbs
Cable length	4 m / 13 ft

## **VIBRATION**

Surface grinding	6 m/s <sup>2</sup>
Uncertainty of measurement K	$1.5 \text{ m/s}^2$
Grinding with sandpaper	$3.6 \text{ m/s}^2$
Uncertainty of measurement K	$1.5 \text{ m/s}^2$

### **NOISE EMISSION**

Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

# Scope of delivery

- Guard
- Inner support flange
- M-Quick flange nut
- Metabo VibraTech (MVT) side handle