

WEV 1500-125 RT (601243000) Angle grinder

Order No. 601243000
EAN 4007430297396



Representative picture



- Powerful and robust angle grinder with speed control and ergonomic soft handle for low-fatigue working, especially overhead
- Powerful motor with good overload capacity
- Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Tool-free adjustable guard; twist-proof
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly - for high user safety
- Electronic soft start for smooth start-up
- Restart protection after power interruption
- Auto-stop carbon brushes to protect the motor

Technical values

KEY FIGURES

| | |
|---------------------|-----------------------|
| Disc-Ø | 125 mm // 5 " |
| Rated input power | 1500 W |
| Output power | 900 W |
| No-load speed | 3500 - 11000 rpm |
| Speed at rated load | 11000 rpm |
| Torque | 4.2 Nm / 37.2 ft. lbs |

| | |
|------------------------------|------------------|
| Spindle thread | M 14 |
| Handle circumference | 138 mm / 5.438 " |
| Weight (without power cable) | 2.4 kg / 5.3 lbs |
| Cable length | 4 m / 13 ft |

VIBRATION

| | |
|------------------------------|----------------------|
| Surface grinding | 9 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 5.3 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

NOISE EMISSION

| | |
|------------------------------|----------|
| Sound pressure level | 87 dB(A) |
| Sound power level (LwA) | 98 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

- Guard
- Inner support flange
- Nut with two holes
- Side handle
- Flat-pin spanners