

## W 9-125 Quick (600374000) Angle grinder

Order No. 600374000  
EAN 4007430240989



Representative picture



- Low fatigue as never before: compact angle grinder with smallest handle circumference in its class for perfect ergonomics
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Restart protection after power interruption
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

### Technical values

#### KEY FIGURES

|                     |               |
|---------------------|---------------|
| Disc-Ø              | 125 mm // 5 " |
| Rated input power   | 900 W         |
| Output power        | 550 W         |
| No-load speed       | 10500 rpm     |
| Speed at rated load | 7500 rpm      |

|                              |                    |
|------------------------------|--------------------|
| Torque                       | 2.5 Nm / 22 in-lbs |
| Spindle thread               | M 14               |
| Handle circumference         | 193 mm / 7.5594 "  |
| Weight (without power cable) | 2.1 kg / 4.6 lbs   |
| Cable length                 | 4 m / 13 ft        |

## VIBRATION

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 6 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

## NOISE EMISSION

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 93 dB(A)  |
| Sound power level (LwA)      | 104 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

- Guard
- Inner support flange
- M-Quick flange nut
- Side handle