

## KHE 5-40 (600391500) Combination hammer

Order No. 600391500 EAN 4061792199255



Representative picture













- Combination hammer with 2 functions: hammer drilling and chiselling
- Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user&#039:s health
- Easily accessible locking switch for chiselling in continuous mode
- Vario-Constamatic (VC)-Full wave electronics for working at customised speeds to suit the application materials, and speeds that remain almost constant even under load
- Thumbwheel for preselection of the speed and impact rate
- · Electronic soft start for precise spot-drilling
- Optimum heat dissipation and low weight thanks to die cast magnesium gear housing
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Restart protection: prevents unintentional start-up after power supply interruption
- Low-dust chiselling and drilling with external dust extraction ESA max (accessories)
- Wear Indication for Carbon Brush
- Service display, e.g. to indicate when the carbon brush needs to be replaced, and an LED indicating mains voltage
- Early warning system thanks to service LED for targeted planning of the carbon brush replacement 8 working hours before switching off

#### Technical values

#### **KEY FIGURES**

8.5 J Max. single blow energy (EPTA)

Maximum impact rate 3000 bpm

Rated input power	1100 W
Drill-Ø concrete with hammer drills	40 mm / 1 9/16 "
No-load speed	350 - 540 rpm
Speed at rated load	540 rpm
Tool holder	SDS-max
Collar diameter	61 mm / 2.4 "
Weight (without power cable)	7.1
Cable length	6 m / 19.7 ft m

## **VIBRATION**

Hammer drilling concrete	$14.6 \text{ m/s}^2$
Uncertainty of measurement K	$1.5 \text{ m/s}^2$
Chiseling	$9.7 \text{ m/s}^2$
Uncertainty of measurement K	$1.5 \text{ m/s}^2$

## **NOISE EMISSION**

Sound pressure level	95 dB(A)
Sound power level (LwA)	106 dB(A)
Uncertainty of measurement K	3 dB(A)

# Scope of delivery

- Side handle
- Drilling depth guide
- Lubricant for tool shank end
- Duster
- Plastic carry case