

KS 55 (600855000) Circular saw

Order No. 600855000
EAN 4007430230409



Representative picture

- Light, compact circular saw for universal construction site use
- Grip area with non-slip soft-grip surface
- Clearly visible cutting indicator for precise sawing after initial cut
- 0° position re-adjustable for highest cutting precision
- Extraction possibility by means of connecting an all-purpose vacuum cleaner

Technical values

KEY FIGURES

Rated input power	1200 W
Output power	670 W
Maximum cutting depth at 90°	55 mm / 2 5/32 "
Maximum cutting depth at 45°	39 mm / 1 17/32 "
Saw blade Ø x bore	160 x 20 mm // 6 1/4 x 0.787 "
Swivel range from / to:	0 / + 47 °
No-load speed	5600 rpm
Speed at rated load	4400 rpm
Max. cutting speed	47 m/s / 154 ft/s
Torque	5 Nm / 44 in-lbs

Weight (without power cable)	4 kg / 8.8 lbs kg
------------------------------	-------------------

Cable length	4 m / 13 ft
--------------	-------------

VIBRATION

Sawing chipboards	3.4 m/s ²
-------------------	----------------------

Uncertainty of measurement K	1.5 m/s ²
------------------------------	----------------------

NOISE EMISSION

Sound pressure level	93 dB(A)
----------------------	----------

Sound power level (LwA)	104 dB(A)
-------------------------	-----------

Uncertainty of measurement K	3 dB(A)
------------------------------	---------

Scope of delivery

- Carbide circular saw blade (18 teeth)
- Parallel guide
- Extraction connector
- Hexagonal wrench