

RSEV 19-125 RT (603825710) Renovation grinder

Order No. 603825710 EAN 4007430313638



Representative picture











- · For effective spot grinding and removal of concrete, screed and coatings with diamond cup wheels
- Maximum productivity thanks to 1,900 Watt strong Metabo Marathon-motor with low weight
- · High torque and overload capacity for demanding applications in continuous use
- Low weight, ideal for sanding walls and ceilings
- · Perfect ergonomics thanks to slim handle for maximum control and easy working overhead
- Working close to edges thanks to integrated folding segment
- Optimum extraction results: spring-mounted brush rim at the protective cover that adapts to any surface and segment height
- · Front handle for safe and uniform guidance when polishing, adjustable without tools
- Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after power supply interruption
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the tool stop unexpectedly
- Connection for dust extraction Ø 35/41 mm

Technical values

KEY FIGURES

Cup wheel \emptyset 125 mm / 5 "

| Torque | 5 Nm / 44 in-lbs |
|---------------|------------------|
| No-load speed | 3800 - 8200 rpm |

| Rated input power | 1900 W |
|------------------------------|------------------|
| Output power | 1240 W |
| Speed at rated load | 6800 rpm |
| Spindle thread | M 14 |
| Weight (without power cable) | 3.5 kg / 7.7 lbs |
| Cable length | 4 m / 13 ft |

VIBRATION

| Surface grinding | 6.94 m/s^2 |
|------------------------------|----------------------|
| Uncertainty of measurement K | 1.5 m/s^2 |

NOISE EMISSION

| Sound pressure level | 92 dB(A) |
|------------------------------|-----------|
| Sound power level (LwA) | 103 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

- Bow-type handle
- Inner support flange
- Nut with two holes
- Diamond cup wheel concrete "professional"
- Flat-pin spanners
- · Plastic carry case