

ASR 35 H ACP (602059000) All-purpose vacuum cleaner

Order No. 602059000 EAN 4007430279316



Representative picture









- · Ideal vacuum cleaner for removal of mould and old insulation in roof and wall areas
- Ideal when sanding painted or coated wood surfaces with lead, nickel, cadmium or chromium content
- Compact vacuum cleaner for liquids and dry solids with commercial registration
- Power socket for a power tool for using the automatical start-up/shut-down of the vacuum cleaner
- AutoCleanPlus: saves both costs and time thanks to automatic MPulse filter cleaning during continuous
 use
- · If the optimum suction performance falls below a certain level, the filters are vibrated immediately
- · Maximum user protection: certified in accordance with EU standard for H class dusts
- · Automatic shut-down when vacuuming liquids once the maximum fill level is reached
- Warning signal on shortfall of the minimum volume flow to protect the user
- Optimum suction power by preselection of the hose diameter
- Automatic trailing mechanism for emptying the suction hose completely
- Antistatic basic equipment prevents static charge when using appropriate accessories
- Sturdy thanks to especially large wheels and castors with wheel stop
- Cable winding mechanism
- Practical accessory case and storage area

Technical values

KEY FIGURES

Air output max.	4380 l/min / 157 cfm
Vacuum	270 hPa (mbar) / 3.6 psi

Filter surface	8600 cm ² / 1333 sq.inch
	, , , , , , , , , , , , , , , , , , , ,

Input power max.	1400 W
Container volume	35 l / 9 gal
Suction hose Ø	35 mm / 1 3/8 "
Hose length	4 m / 15 ft
Weight	16 kg / 35.3 lbs
Cable length	8 m / 26 ft

NOISE EMISSION

Sound pressure level 69 dB(A)

Scope of delivery

- Antistatic suction hose (\emptyset 35 mm / 4 m)
- Connection bush Ø 41/48 mm
- · Handle adapter
- 2 Plastic suction tubes
- 2 HEPA polyester filter cassettes
- PE Disposal bag
- Crevice nozzle
- Floor nozzle (300 mm wide)