

SPA 1200 (601205000) Chip and dust extraction unit

Order No. 601205000 EAN 4007430210265



Representative picture

- Raw air extraction device for (semi) stationary wood processing machines (observe country-specific regulations!)
- Significantly reduces dust content
- Filter material of dust class L
- Integrated grounding as protection from electrostatic charge
- Quick change of the application location by means of wheeled unit and simple connection
- Stable stand with supported chip collection bag
- Comprehensive range of accessories: automatic switch-on devices, filter cartridges, hoses and adapters

Technical values

KEY FIGURES

Dimensions	830 x 450 x 1600 mm // 2.8 x 1.5 x 5.3 ft
Maximum vacuum	1600 Pa / 0.2 psi
Maximum volume flow	900 m ³ /h / 237755 gal/h
Filter surface	1 m ² / 1550 sq.inch
Hose connection Ø	100 mm / 4 "
Chip bag capacity	65 l / 17 gal
Mains voltage	220 - 240 V
Rated input power	0.55 kW

	G ,
Cable length	3 m
NOISE EMISSION	
Sound pressure level	85 dB(A)
Sound power level (LwA)	98 dB(A)
Uncertainty of measurement K	3 dB(A)

22 kg / 48.5 lbs

Scope of delivery

Weight

- Suction hose 100 x 2500 mm
- Filter bag made of needle felt
- Chip Collection Bag