

## HHW 3500/25 Inox (600969000) Domestic waterwork

Order No. 600969000  
EAN 4007430239556



Representative picture



- For automatic water supply, for garden irrigation and groundwater pumping as well as pumping, pumping empty, circulation of clear water
- Pressure vessel for energy-saving and low-noise provision of water
- Pressure switch at the tank for automatic activation in case of increased water demand
- Maintenance-free capacitor motor
- Overload protection: protects the motor from overheating
- High-quality slip seal system for long service life
- Durable stainless steel pump housing
- Separate water filling opening for simple operation of the pump
- Water drain plug (removable without tools) for protection in case of frost
- For garden irrigation with 1 or 2 sprinklers
- For single phase alternating current

### Technical values

#### KEY FIGURES

|                         |                      |
|-------------------------|----------------------|
| Rated input power       | 900 W                |
| Maximum delivery rate   | 3500 l/h / 925 gal/h |
| Maximum delivery height | 45 m / 148 ft        |
| Maximum pressure        | 4.5 bar / 65.3 psi   |
| Maximum suction height  | 8 m / 26 ft          |

|                              |   |
|------------------------------|---|
| Switch-on pressure approx.   | 1.4 bar / 20.3 psi                            |
| Switch-off pressure approx.  | 3.2 bar / 46.4 psi                            |
| Suction port                 | 1" female thread                              |
| Discharge port               | 1" female thread                              |
| Tank capacity, approximately | 24 l / 6.3 gal                                |
| Pump housing                 | Stainless steel                               |
| Protection type IP           | IP X4   |
| Drive shaft                  | Stainless steel                               |
| Tank                         | Steel   |
| Number of impellers          | 1   |
| Dimensions                   | 484 x 270 x 584 mm // 19 1/16 x 10 5/8 x 23 " |
| Weight                       | 14.6 kg / 32 lbs                              |
| Cable length                 | 1.5 m / 5 ft                                  |

## NOISE EMISSION

|                              |            |
|------------------------------|------------|
| Sound pressure level         | 68 dB(A)   |
| Sound power level (LwA)      | 81.1 dB(A) |
| Uncertainty of measurement K | 2.9 dB(A)  |

## Scope of delivery

- Check Valve
- Fabric Sealing Tape