

DP 28-10 S Inox (604112000) Drainage Pump

Order No. 604112000
EAN 4007430221544



Representative picture



- For effective pumping of large quantities of dirty water, rain water, ground water and water on construction sites
- Ideal motor cooling by means of the conveyed medium even when the water level is low
- Double mechanical seal with oil chamber for ideal protection of the pump if the water is very dirty
- Self-cleaning Vortex-impeller to minimise blockages
- Designed for continuous mode with S1 motor operating mode
- Overload protection: protects the motor from overheating
- Float switch for automatic mode
- Suitable for mobile and stationary use thanks to ergonomic handles and stability
- Durable pump housing made of non-corrosive, high-quality stainless steel

Technical values

KEY FIGURES

| | |
|-------------------------|------------------------|
| Rated input power | 1850 W |
| Maximum delivery rate | 28000 l/h / 7397 gal/h |
| Maximum delivery height | 17 m / 56 ft |
| Maximum pressure | 1.7 bar / 24.7 psi |
| Maximum immersion depth | 7 m / 23 ft |
| Discharge port | 1 1/2" female thread |

| | |
|-----------------------------|---|
| Pump housing | Stainless steel |
| Protection type IP | IP 68 |
| Maximum particle size up to | 10 mm / 3/8 " |
| Number of impellers | 1 |
| Dimensions | 215 x 215 x 465 mm // 8 15/32 x 8 15/32 x 18 5/16 " |
| Weight | 18.5 kg / 40.8 lbs |
| Cable length | 10 m / 33 ft |

Scope of delivery

- Float switch