

Order No. 603180620
EAN 4061792211674



Representative picture



Technical values

KENNWERTE

Type of battery pack	LiHD
Battery voltage	18 V
Battery pack capacity	2 x 5.5 Ah
Maximum torque, soft	65 Nm / 575 in-lbs
Maximum torque, hard	130 Nm / 1150 in-lbs
Adjustable torque	1 - 18 Nm // 8.9 - 159.3 in-lbs
Drill Ø steel	16 mm / 5/8 "
Drill-Ø soft wood	68 mm / 2.68 "
No-load speeds	0 - 450 / 0 - 2000 / 0 - 4000 rpm
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Collar diameter	43 mm / 1.69 "
Weight without battery pack	2 kg / 4.4 lbs

Weight with battery pack	3 kg / 6.6 lbs
--------------------------	----------------

VIBRATION

Drilling in metal	2.5 m/s ²
-------------------	----------------------

Uncertainty of measurement K	1.5 m/s ²
------------------------------	----------------------

GERÄUSCHEMISSION

Sound pressure level	75 dB(A)
----------------------	----------

Sound power level (LwA)	85 dB(A)
-------------------------	----------

Uncertainty of measurement K	3 dB(A)
------------------------------	---------

Scope of delivery

- Futuro Top quick-change chuck "QuickPlus"
- Side handle
- C-wrench
- 2 LiHD battery packs (18 V/5.5 Ah)
- Quick charger ASC 145 "AIR COOLED"
- metaBOX 145 L