

Order No. 602358520
EAN 4061792187801



Representative picture



Technical values

KENNWERTE

Type of battery pack	LiPOWER
Battery voltage	18 V
Battery pack capacity	2 x 5.2 Ah
Maximum torque, soft	65 Nm / 575 ft. lbs
Pulse torque	65 Nm / 575 in-lbs
Maximum torque, hard	130 Nm / 1151 ft. lbs
Adjustable torque	1 - 20 Nm // 9 - 177 in-lbs
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	68 mm / 2.68 "
No-load speeds	0 - 550 / 0 - 2000 rpm
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Collar diameter	43 mm / 1 11/16 "

Weight without battery pack	1.7 kg / 3.7 lbs
-----------------------------	------------------

Weight with battery pack	2.4 kg / 5.3 lbs
--------------------------	------------------

VIBRATION

Drilling in metal	2.2 m/s ²
-------------------	----------------------

Uncertainty of measurement K	1.5 m/s ²
------------------------------	----------------------

GERÄUSCHEMISSION

Sound pressure level	76 dB(A)
----------------------	----------

Sound power level (LwA)	87 dB(A)
-------------------------	----------

Uncertainty of measurement K	3 dB(A)
------------------------------	---------

Scope of delivery

- Keyless chuck
- Bit holder
- Side handle
- Belt hook and bit case
- Belt hook
- 2 LiPOWER battery packs (18 V/5.2 Ah)
- Charger ASC 55 "AIR COOLED"
- metaBOX 145 L