

Order No. 601036000
EAN 4061792177994



Representative picture

Technical values

KENNWERTE

Type of battery pack	LiPOWER
Battery voltage	12 V
Battery pack capacity	1 x 2 Ah
Maximum torque, soft	17 Nm / 150 in-lbs
Maximum torque, hard	40 Nm / 354 in-lbs
Adjustable torque	0.5 - 5 Nm // 4 - 44 in-lbs
Drill Ø steel	10 mm / 3/8 "
Drill-Ø soft wood	18 mm / 23/32 "
No-load speeds	0 - 360 / 0 - 1400 rpm
Chuck capacity	1 - 10 mm // 1/32 - 3/8 "
Weight without battery pack	0.84 kg / 1.9 lbs
Weight with battery pack	1.1 kg / 2.4 lbs

VIBRATION

Drilling in metal	3 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Screwdriving without impact	2.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²

GERÄUSCHEMISSION

Sound pressure level	64 dB(A)
Sound power level (LwA)	75 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

- Keyless chuck
- Belt hook and bit case
- LiPOWER Battery Pack (12 V/2.0 Ah)
- Charger SC 36