

# KH 18 LTX BL 24 (601713860) Cordless combination hammer

Order No. 601713860  
EAN 4061792218512



Representative picture



- Very lightweight, compact cordless hammer with brushless motor for low-fatigue drilling in any working position
- Maximum drill performance, efficiency and service life thanks to brushless technology and high-performance hammer action
- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user's health
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Electronic soft start for precise spot-drilling
- Safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- LED work light for optimum view of the drilling site
- Dust-free drilling with external dust extraction ESA plus (accessory)
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical values

### KEY FIGURES

|                                |       |
|--------------------------------|-------|
| Battery voltage                | 18 V  |
| Max. single blow energy (EPTA) | 2.2 J |

|                                     |                   |
|-------------------------------------|-------------------|
| Maximum impact rate                 | 4750 bpm          |
| Drill-Ø concrete with hammer drills | 24 mm / 1 "       |
| Drill-Ø masonry with core bits      | 82 mm / 3 7/32 "  |
| Drill Ø steel                       | 13 mm / 1/2 "     |
| Drill-Ø soft wood                   | 30 mm / 1 3/16 "  |
| No-load speed                       | 0 - 1280 rpm      |
| Tool holder                         | SDS-plus          |
| Weight without battery pack         | 2.7 kg / 5.95 lbs |

## VIBRATION

|                              |                       |
|------------------------------|-----------------------|
| Hammer drilling concrete     | 13.6 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |
| Chiseling                    | 9.2 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |

## NOISE EMISSION

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 90 dB(A)  |
| Sound power level (LwA)      | 101 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

- rubber-coated side handle
- Drilling depth guide
- Plastic carry case
- without battery pack, without charger