

SBE 650 (600742420) Impact drill

Order No. 600742420
EAN 4061792201477



Representative picture

- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Thumbwheel for Speed Preselection
- Forward and reverse rotation
- Spindle with hexagonal recess for screwdriver bits for working without chuck

Technical values

KEY FIGURES

| | |
|---------------------|--------------------|
| Rated input power | 650 W |
| Output power | 320 W |
| Maximum torque | 10 Nm // 88 in-lbs |
| Drill-Ø masonry | 16 mm / 5/8 " |
| Drill-Ø concrete | 14 mm / 9/16 " |
| Drill Ø steel | 13 mm // 1/2 " |
| Drill-Ø soft wood | 30 mm // 1 3/16 " |
| Speed at rated load | 1500 rpm |
| Maximum impact rate | 44800 bpm |
| Gears | 1 |

| | |
|-------------------------------------|-----------------------------|
| Chuck capacity | 1.5 - 13 mm // 1/16 - 1/2 " |
| Collar diameter | 43 mm / 1 11/16 " |
| Drill spindle with hexagonal recess | 6.35 mm / 1/4 " |
| Drill spindle thread | 1/2 " - 20 UNF |
| Chuck clamping type | Geared Chucks |
| Weight (without power cable) | 1.8 kg |
| Cable length | 2.5 m / 8 ft m |

VIBRATION

| | |
|------------------------------|-----------------------|
| Drilling in metal | 5.8 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Impact drilling concrete | 24.4 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

NOISE EMISSION

| | |
|------------------------------|-----------|
| Sound pressure level | 91 dB(A) |
| Sound power level (LwA) | 102 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

- Geared Chucks
- Chuck Keys
- Side handle
- Drilling depth guide