

## KHE 2660 Quick (600663510) Combination hammer

Order No. 600663510 EAN 4007430309624



Representative picture









- · Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Metabo Quick: quick change between SDS Plus hammer chuck and keyless chuck for many different applications
- Perfect ergonomics thanks to the centre of gravity being near the hand and optimised handle contour
- · Bottom switch protected against damage and dust
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Metabo Marathon-motor with dust protection for long service life
- High performance hammer action, precisely mounted in a housing made of aluminium alloy: longlasting and robust
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Lockable switch for comfortable working in continuous operation
- · Cable-protecting ball joint for optimal freedom of motion when working
- With metaBOX, the intelligent solution for transport and storage

#### Technical values

#### **KEY FIGURES**

Max. single blow energy (EPTA)	3 Ј
Maximum impact rate	4300 bpm
Rated input power	850 W
Drill-Ø concrete with hammer drills	26 mm / 1 1/32 "

Drill-Ø masonry with core bits	68 mm / 2 11/16 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	32 mm / 1 1/4 "
No-load speed	0 - 1100 rpm
Speed at rated load	830 rpm
Tool holder	SDS-plus
Collar diameter	50 mm / 1 31/32 "
Weight (without power cable)	3.1 kg / 6.9 lbs
Cable length	4 m / 13 ft m

### **VIBRATION**

Hammer drilling concrete	$12.9 \text{ m/s}^2$
Uncertainty of measurement K	2.4 m/s <sup>2</sup>
Chiseling	$8.5 \text{ m/s}^2$
Uncertainty of measurement K	$1.5 \text{ m/s}^2$

### **NOISE EMISSION**

Sound pressure level	89 dB(A)
Sound power level (LwA)	99 dB(A)
Uncertainty of measurement K	3 dB(A)

# Scope of delivery

- Hammer chuck for tools with SDS-plus shank end
- rubber-coated side handle
- Drilling depth guide
- metaBOX 145 L