

KH 5-40 (600763520) Combination hammer

Order No. 600763520 EAN 4007430331847



Representative picture





- · Combination hammer with 2 functions: hammer drilling and chiselling
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- · Robust die cast aluminium gear housing for optimum heat dissipation and long service life

Technical values

KEY FIGURES

Max. single blow energy (EPTA)	7.1 J
Maximum impact rate	2800 bpm
Rated input power	1100 W
Drill-Ø concrete with hammer drills	40 mm / 1 9/16 "
Drill-Ø masonry with core bits	105 mm / 4 1/8 "
No-load speed	620 rpm
Tool holder	SDS-max
Collar diameter	61 mm / 2.4 "
Weight (without power cable)	7.1 kg / 15.7 lbs

Cable length	4 m / 13 ft m
VIBRATION	
Hammer drilling concrete	16.5 m/s^2
Uncertainty of measurement K	1.5 m/s^2
Chiseling	13.3 m/s^2
Uncertainty of measurement K	1.5 m/s^2
NOISE EMISSION	
Sound pressure level	95 dB(A)
Sound power level (LwA)	106 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

- rubber-coated side handle
- Drilling depth guide
- Lubricant for tool shank end
- Plastic carry case