

KH 5-40 (600763620) Combination hammer

Order No. 600763620
EAN 4007430331861



Representative picture



- Combination hammer with 2 functions: hammer drilling and chiselling
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Robust die cast aluminium gear housing for optimum heat dissipation and long service life

Technical values

KEY FIGURES

Max. single blow energy (EPTA)	7.1 J
Maximum impact rate	2800 bpm
Drill-Ø concrete with hammer drills	40 mm / 1 9/16 "
Drill-Ø masonry with core bits	105 mm / 4 1/8 "
No-load speed	620 rpm
Tool holder	SDS-max
Collar diameter	61 mm / 2.4 "
Weight (without power cable)	7.1 kg / 15.7 lbs
Cable length	2.5 m / 8.2 ft m

VIBRATION

Hammer drilling concrete	16.5 m/s ²
--------------------------	-----------------------

Uncertainty of measurement K	1.5 m/s ²
------------------------------	----------------------

Chiseling	13.3 m/s ²
-----------	-----------------------

Uncertainty of measurement K	1.5 m/s ²
------------------------------	----------------------

NOISE EMISSION

Sound pressure level	95 dB(A)
----------------------	----------

Sound power level (L _{WA})	106 dB(A)
--------------------------------------	-----------

Uncertainty of measurement K	3 dB(A)
------------------------------	---------

Scope of delivery

- rubber-coated side handle
- Drilling depth guide
- Lubricant for tool shank end
- Plastic carry case