

KHE 3560 Q (600811520) Combination hammer

Order No. 600811520
EAN 4061792264038



Representative picture



- Metabo's most powerful SDS-plus combination hammer for quick drilling and efficient chiseling in concrete and masonry
- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Metabo Quick: quick change between SDS Plus hammer chuck and keyless chuck for many different applications
- Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user's health
- Perfect ergonomics thanks to the centre of gravity being near the hand and optimised handle contour
- Can be switched to anticlockwise rotation to easily loosen tilted tool attachments
- Optional reduction of speed and impact energy for starting a drill hole or working in softer materials
- Double safety when the drill bit jams: No kick-back thanks to the mechanic decoupling plus ultra-fast sensor-controlled shutdown
- Restart protection: prevents unintentional start-up after power supply interruption
- Overload protection: protects the motor from overheating
- LED work light for optimum view of the drilling site
- Wear Indication for Carbon Brush
- With metaBOX, the intelligent solution for transport and storage

Technical values

KEY FIGURES

| | |
|--------------------------------|----------|
| Max. single blow energy (EPTA) | 4.2 J |
| Maximum impact rate | 4350 bpm |

| | |
|-------------------------------------|-----------------|
| Rated input power | 1050 W |
| Drill-Ø concrete with hammer drills | 32 mm / 1 1/4 " |
| No-load speed | 0 - 810 rpm |
| Speed at rated load | 810 rpm |
| Tool holder | SDS-plus |
| Collar diameter | 60 mm / 2 3/8 " |
| Weight (without power cable) | 5 kg / 11 lbs |
| Cable length | 3.9 m |

VIBRATION

| | |
|------------------------------|-----------------------|
| Hammer drilling concrete | 17.2 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Chiseling | 12.8 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

NOISE EMISSION

| | |
|------------------------------|-----------|
| Sound pressure level | 93 dB(A) |
| Sound power level (LwA) | 101 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

- Hammer chuck for tools with SDS-plus shank end
- Keyless chuck for tools with cylindrical shank
- Side handle
- Drilling depth guide
- metaBOX 185 XL