

## WEA 17-125 Quick (600534190) Angle grinder

Order No. 600534190

EAN 4007430246080



Representative picture



- Maximum productivity: 1,700 Watt angle grinder with the power of a large grinder and the compactness of a small one for quickest material removal on industrial applications
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Best anti-vibration system: integrated auto-balancer for up to 50% less hand-arm vibrations, longer service life of the machine and up to twice the service life of the grinding wheels
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical values

### KEY FIGURES

|                   |               |
|-------------------|---------------|
| Disc-Ø            | 125 mm // 5 " |
| Rated input power | 1700 W        |

|                              |                    |
|------------------------------|--------------------|
| Output power                 | 1040 W             |
| No-load speed                | 11000 rpm          |
| Speed at rated load          | 11000 rpm          |
| Torque                       | 3.7 Nm / 33 in-lbs |
| Spindle thread               | M 14               |
| Handle circumference         | 206 mm / 8 1/8 "   |
| Weight (without power cable) | 2.5 kg / 5.5 lbs   |
| Cable length                 | 4 m / 13 ft        |

## VIBRATION

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 4 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 3 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

## NOISE EMISSION

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 93 dB(A)  |
| Sound power level (LwA)      | 104 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

- Guard
- Inner support flange
- M-Quick flange nut
- Metabo VibraTech (MVT) side handle