

WEV 850-125 (603611520) Angle grinder

Order No. 603611520
EAN 4061792220812



Representative picture



- Robust, universal and economical: powerful angle grinder for any application
- Powerful motor with good overload capacity
- Thumbwheel controlled Vario-Constamatic (VC)-Full wave electronics ideal for working on materials requiring customised speeds, and at speeds which remain almost constant under load
- Twist-proof guard
- Electronic overload protection, soft start and restart protection
- Auto-stop carbon brushes to protect the motor

Technical values

KEY FIGURES

| | |
|---------------------|------------------|
| Disc-Ø | 125 mm // 5 " |
| Rated input power | 850 W |
| Output power | 480 W |
| No-load speed | 3000 - 11500 rpm |
| Speed at rated load | 8500 rpm |
| Torque | 2 Nm / 18 in-lbs |
| Spindle thread | M 14 |

| | |
|------------------------------|------------------|
| Handle circumference | 179 mm / 7.063 " |
| Weight (without power cable) | 1.9 kg / 4.2 lbs |
| Cable length | 2.5 m / 8 ft |

VIBRATION

| | |
|------------------------------|----------------------|
| Surface grinding | 8 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

NOISE EMISSION

| | |
|------------------------------|----------|
| Sound pressure level | 88 dB(A) |
| Sound power level (LwA) | 99 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

- Guard
- Inner support flange
- Nut with two holes
- Side handle
- Flat-pin spanners
- Plastic carry case