

## TS 254 M (610254390) Table saw

Order No. 610254390  
EAN 4061792180369



Representative picture



- Compact mobile table saw with impressive cutting performance and high comfort for working
- Anti-twist tubular frame construction for highest demands on the building site and during installations
- Cables and all add-on components for transport can be stored on the casing
- Powerful motor with electronic overload protection
- Motor brake for quick stop of the saw blade in 3 seconds
- Restart protection: prevents unintentional start-up after power supply interruption
- Soft start for long service life of motor and drive
- Precisely adjustable parallel guide / rip fence with double clamping and quick fastening
- Precise saw blade inclination via gear guide
- Automatic resetting to 0 – 45 ° after undercuts
- Easy saw blade change with spindle lock
- Splitting wedge can be countersunk without tools for transport
- Precise, extendable table width extension for extra large working surfaces

## Technical values

### KEY FIGURES

|                               |                                                  |
|-------------------------------|--------------------------------------------------|
| Dimensions                    | 669 x 748 x 334 mm // 26.343 x 29.437 x 13.156 " |
| Working height                | 334 mm // 13.15 "                                |
| Cutting height                | 0 - 80 mm // 0 - 3.15 "                          |
| Maximum cutting height 90/45° | 80 / 48 mm // 3.15 / 1.87 "                      |

|                                       |                             |
|---------------------------------------|-----------------------------|
| Maximum cutting width at rip fence    | 520 mm / 20.46 "            |
| Maximum material width at mitre fence | 195 mm / 7.68 "             |
| No-load speed                         | 4200 rpm                    |
| Cutting speed                         | 56 m/s / 184 ft/s           |
| Saw blade                             | 254 x 30 mm // 10 x 1.181 " |
| Saw blade swivel range                | -1.5 - 46.5 °               |
| Mains voltage                         | 110 - 120 V                 |
| Rated input power S1 100%             | 1500 W                      |
| Rated input power S6 20%              | 1800 W                      |
| Weight                                | 24.4 kg / 54 lbs            |
| Cable length                          | 2.3 m / 80.56 "             |

## NOISE EMISSION

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 92 dB(A)  |
| Sound power level (LwA)      | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

- Carbide saw blade with alternately bevel-ground tips (40 teeth)
- Rip Fence
- Mitre Fence
- Table Length Extension
- Table width extension (right)
- Push stick