

# DH 330 (0200033019) Bench Thicknesser

Order No. 0200033019 EAN 4003665424484



Representative picture



- Ideal for mobile use due to low weight
- Stable gear for uniform work piece feed
- · Convenient height adjustment with crank handle
- Easy setting of common passage heights using stop points
- Powerful universal motor for powerful lugging drive and even planing result
- Restart protection: prevents unintentional start-up after power supply interruption
- · Precise thickness adjustment for quick and exact planing
- Large feed and exit tables support the conveyance of long materials
- · Planing locking mechanism prevents unintentional adjustment of the chip removal setting

## **Technical values**

#### **KEY FIGURES**

| Dimensions                     | 579 x 857 x 574 mm // 1.9 x 2.9 x 1.9 ft |
|--------------------------------|--|
| Chip removal bench thicknesser | 0 - 3 mm // 0 - 1/8 "                    |
| Material thickness table       | Cast aluminium / special steel aluminium |
| Thickness table L x W          | 840 x 330 mm // 33 x 13 "                |
| Passage height/width           | 152 / 330 mm // 6 / 13 "                 |
| Feed rate                      | 7.51 m/min / 25 ft/min                   |

| Diameter of blade shaft    | 47 mm / 1 7/8 "  |
|----------------------------|------------------|
| Number of blades           | 2                |
| Revolutions of blade shaft | 9800 rpm         |
| Mains voltage              | 220 - 240 V      |
| Rated input power          | 1800 W           |
| Weight                     | 35 kg / 77.2 lbs |

## **NOISE EMISSION**

Uncertainty of measurement K 4 dB(A)

## Scope of delivery

- 2 integrated HSS reversible planer blades
- Push stick
- Extraction Nozzles