

## WEPBA 19-180 Quick RT (601099000) Angle grinder

Order No. 601099000 EAN 4007430314277



Representative picture





















- The most powerful one with full 1,900 Watt for industrial processing of weld seams and a cutting depth like a large angle grinder ( $\emptyset$  230 mm) with only half the weight
- Perfect ergonomics thanks to slim handle for maximum control and easy working overhead
- Metabo Marathon-motor with new cooling and carbon brush system for twice the service life
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- M-Quick System for tool-free disc change at the touch of a button
- Tool-free adjustable guard; twist-proof
- Reduced vibrations for low-fatigue working thanks to Metabo VibraTech (MVT) side handle and integrated Auto-balancer
- Highest degree of user safety thanks to patented, mechanical disc brake and deadman & #039;s switch: disc stop in 2 seconds after releasing even in case of a power cut
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Electronic soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or
- Auto-stop carbon brushes to protect the motor

#### Technical values

#### **KEY FIGURES**

180 mm Disc-Ø

1900 W Rated input power

Output power	1240 W
No-load speed	8200 rpm
Speed at rated load	8200 rpm
Torque	5 Nm
Spindle thread	M 14
Handle circumference	138 mm
Weight (without power cable)	2.9 kg
Cable length	4 m

### **VIBRATION**

Surface grinding	$4.9 \text{ m/s}^2$
Uncertainty of measurement K	$1.5 \text{ m/s}^2$
Grinding with sandpaper	5 m/s <sup>2</sup>
Uncertainty of measurement K	$1.5 \text{ m/s}^2$

#### **NOISE EMISSION**

Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

# Scope of delivery

- Guard
- Inner support flange
- M-Quick flange nut
- Metabo VibraTech (MVT) side handle