


Jigsaw blades "clean wood premium"

- clean and precise cuts with a very long tool life



Representative picture

Material suitability	Version	Material	Useable length	Thickness	Tooth pitch	Corresponds to Bosch type	Sales unit	Order No.
especially for laminate / Laminated flooring / kitchen worktops 3-30 mm / coated boards / for clean cuts / Caution: deactivate the pendulum stroke!	clearance angle ground / tooth ground / reverse serration	BiM	74 mm	1.25 mm	2,5 mm	T 101 BRF	5	623686000
especially for laminate / Laminated flooring / hard wood / Soft wood / coated boards / Plywood / especially for curved cuts / for clean cuts	clearance angle ground / tooth ground / tapered	BiM	57 mm	1.25 mm	1,4 mm	T 101 AOF	5	623695000
hard wood / Soft wood / coated boards 4-60 mm	clearance angle ground / tooth ground	BiM	91 mm	1.5 mm	3,0 mm	T 301 CDF	5	623696000
especially for laminate / Laminated	clearance angle ground /	BiM	74 mm	1.25 mm	1,7 mm	T 101 AIF	5	623948000

Material suitability	Version	Material	Useable length	Thickness	Tooth pitch	Corresponds to Bosch type	Sales unit	Order No.
flooring / hard wood / Soft wood / coated boards / plastics 2-30 mm / for clean cuts	tooth ground / tapered							
hard wood / Soft wood / Laminated flooring / coated boards / plastics 3-30 mm / for clean cuts / saw blade with insertion head	clearance angle ground / tooth ground	BiM	74 mm / 3 " mm	1.25 mm	2,7 mm	T 101 BF	5	623975000
hard wood / Soft wood / chipboards / glued woods 5-80 mm / fibreglass reinforced plastics 5-30 mm / for fast cuts	clearance angle ground / tooth ground	BiM	105 mm	1.5 mm	3,0 mm	T 301 CLF	5	623977000
perfect, splinter-free cutting results on both sides / for fast cuts	clearance angle ground / tooth ground	HCS	93 mm	1.5 mm	2,2 mm	T 308 B	5	623998000

Material suitability	Version	Material	Useable length	Thickness	Tooth pitch	Corresponds to Bosch type	Sales unit	Order No.
/ Soft wood / Caution: deactivate the pendulum stroke!								
perfect, splinter-free cutting results on both sides / for fast cuts / hard wood / Caution: deactivate the pendulum stroke!	clearance angle ground / tooth ground	BiM	93 mm	1.5 mm	2,2 mm	T 308 BF	5	623999000