



Representative picture

Suction Hoses

- For connection to the suction side of all garden pumps and domestic waterworks/ automatic domestic water systems with 1½"; female thread
- Suitable for drawing from wells, cisterns, ponds or streams
- 1½"; suction hose, transparent, with incorporated rigid PVC coil, buckling-proof and non-abrasive
- Check valve prevents water from flowing back for fast suction and pumping after interruption
- Strainer with shackle to attach a floating ball
- Consisting of:
 - 1½"; Suction hose
 - Hinge bolt clamp, galvanised steel
 - Brass suction high pressure coupling, 1½"; nozzle
 - Brass quick-action coupling, 1½"; male thread
 - Brass hose nozzle/O-ring, 1½"; male thread
 - Brass check valve, 1½"; female thread with strainer, special steel

Inner Ø	Wall thickness	Bending radius	Length	Operating pressure	Burst pressure	Temperature resistance	Water column (vacuum)	Order No.
25 mm	2.5 mm	110 mm	4 m / 157 1/2 "	2.5 bar / 36 psi	7 bar / 102 psi	-5 - 60 °C	6 m	628797000
25 mm	2.5 mm	110 mm	7 m / 275 19/32 "	2.5 bar / 36 psi	7 bar / 102 psi	-5 - 60 °C	6 m	628798000