



Futuro Top keyless chucks, R

- The first impact-proof keyless chuck, with integrated spring-loaded bit clamping mechanism and dual dust protection
- Keyless for quick tool change
- Firm grip of clamped tools even under the toughest loads
- The oil-resistant, hard-wearing rubber bellows system protects the thread and the precision press fit from dust and dirt
- For clockwise rotating drills only

Representative picture

Clamping width	Female thread	Outer Ø	Length (closed)	Weight	Order No.
1 - 10 mm // 1/32 - 3/8 "	3/8" - 24 UNF	42.8 mm / 1.69 "	77 mm / 3.03 "	0.35 kg / 0.77 lbs	636215000
1 - 13 mm // 1/32 - 1/2 "	3/8" - 24 UNF	42.8 mm / 1.69 "	89 mm / 3 1/2 "	0.5 kg / 1.1 lbs	636225000
1 - 13 mm // 1/32 - 1/2 "	1/2" - 20 UNF	42.8 mm / 1.69 "	89 mm / 3 1/2 "	0.5 kg / 1.1 lbs	636226000
1 - 13 mm // 1/32 - 1/2 "	B16	42.8 mm / 1.69 "	103 mm / 4.06 "	0.6 kg / 1.32 lbs	636227000
3 - 16 mm // 1/8 - 5/8 "	B16	50 mm / 2 "	113 mm / 4 7/16 "	1 kg / 2.2 lbs	636242000

Clamping width	Female thread	Outer Ø	Length (closed)	Weight	Order No.
3 - 16 mm // 1/8 - 5/8 "	B18	50 mm / 2 "	113 mm / 4 7/16 "	1 kg / 2.2 lbs	636243000
1 - 13 mm // 1/32 - 1/2 "	1/2" - 20 UNF	42.8 mm / 1.69 "	89 mm / 3 1/2 "	0.5 kg / 1.1 lbs	636602000