



Futuro R keyless chucks

- Keyless clamping of insertion tools to hand-held and fixed drilling machines
- The chuck readjusts its tension to match the increasing cutting pressure on the cutting bit
- The chuck can be opened easily by hand even after the toughest drilling jobs
- For maximum load
- For clockwise rotating drills only
- Not impact-proof

Representative picture

Clamping width	Female thread	Outer Ø	Length (closed)	Weight	Order No.
1 - 10 mm // 1/32 - 3/8 "	3/8" - 24 UNF	37.5 mm / 1.48 "	77 mm / 3.03 "	0.35 kg / 0.77 lbs	636321000
1 - 10 mm // 1/32 - 3/8 "	1/2" - 20 UNF	37.5 mm / 1.48 "	77 mm / 3.03 "	0.35 kg / 0.77 lbs	636322000
1 - 13 mm // 1/32 - 1/2 "	3/8" - 24 UNF	40.5 mm / 1.59 "	89 mm / 3 1/2 "	0.6 kg / 1.32 lbs	636341000
1 - 13 mm // 1/32 - 1/2 "	1/2" - 20 UNF	40.5 mm / 1.59 "	89 mm / 3 1/2 "	0.6 kg / 1.32 lbs	636342000
1 - 13 mm // 1/32 - 1/2 "	B16	40.5 mm / 1.59 "	103 mm / 4.06 "	0.6 kg / 1.32 lbs	636343000

Clamping width	Female thread	Outer Ø	Length (closed)	Weight	Order No.
1 - 13 mm // 1/32 - 1/2 "	1/2" - 20 UNF	47.5 mm / 1.87 "	111 mm / 4 3/8 "	0.8 kg / 1.76 lbs	636351000
1 - 13 mm // 1/32 - 1/2 "	B16	47.5 mm / 1.87 "	111 mm / 4 3/8 "	0.8 kg / 1.76 lbs	636353000
3 - 16 mm // 1/8 - 5/8 "	5/8" - 16 UN	50 mm / 1.97 "	113 mm / 4 7/16 "	1 kg / 2.2 lbs	636361000
3 - 16 mm // 1/8 - 5/8 "	B16	50 mm / 1.97 "	113 mm / 4 7/16 "	1 kg / 2.2 lbs	636362000
3 - 16 mm // 1/8 - 5/8 "	B18	50 mm / 1.97 "	113 mm / 4 7/16 "	1 kg / 2.2 lbs	636363000