



Geared chucks with key, clockwise rotation

- Tried and tested 1000 times
- The chuck for every type of job
- With female thread or female taper for hand-held or fixed drills as well as for hand-held impact drills
- The clamping force remains constant during drilling and impact drilling
- For clockwise rotating drills only

Representative picture

Clamping width	Female thread	Outer Ø	Length (closed)	Weight	Key size	Order No.
0.5 - 6.5 mm // 1/32 - 1/4 "	3/8" - 24 UNF	30 mm / 1.18 "	53 mm / 2.09 "	0.17 kg / 0.37 lbs kg	1	635008000
1.5 - 13 mm // 1/16 - 1/2 "	B16	42.5 mm / 1.67 "	78 mm / 3.06 "	0.35 kg / 0.77 lbs kg	2	635036000
3 - 16 mm // 1/8 - 5/8 "	B18	50 mm / 1.97 "	94.5 mm / 3.72 "	0.63 kg / 1.39 lbs kg	3	635049000
3 - 16 mm // 1/8 - 5/8 "	B16	50 mm / 1.97 "	86 mm / 3 3/8 "	0.64 kg / 1.41 lbs kg	3	635050000
3 - 16 mm // 1/8 - 5/8 "	1/2" - 20 UNF	50 mm / 1.97 "	87.5 mm / 3.44 "	0.6 kg / 1.32 lbs kg	3	635054000

Clamping width	Female thread	Outer Ø	Length (closed)	Weight	Key size	Order No.
3 - 16 mm // 1/8 - 5/8 "	5/8" - 16 UN	50 mm / 1.97 "	87.5 mm / 3.44 "	0.59 kg / 1.3 lbs kg	3	635056000
5 - 20 mm // 3/16 - 25/32 "	B22	65 mm / 2.56 "	113 mm / 4.45 "	0.75 kg	4	635058000
1.5 - 13 mm // 1/16 - 1/2 "	1/2" - 20 UNF	42.5 mm / 1.67 "	74 mm / 2.91 "	0.31 kg / 0.68 lbs kg	2	635302000