



Geared chucks with key, R + L

- Tried and tested 1000 times
- The chuck for every type of job
- With female thread or female taper for hand-held or fixed drills as well as for hand-held impact drills
- The clamping force remains constant during drilling and impact drilling
- Drills through using locking screw for clockwise and anti-clockwise operating machines

Representative picture

Clamping width	Female thread	Outer Ø	Length (closed)	Weight	Key size	Order No.
1 - 10 mm // 1/32 - 3/8 "	1/2" - 20 UNF	33.3 mm / 1.31 "	61 mm / 2.41 "	0.17 kg / 0.37 lbs	2	635252000
3 - 16 mm // 1/8 - 5/8 "	5/8" - 16 UN	50 mm / 1.97 "	87.5 mm / 3.44 "	0.6 kg / 1.32 lbs	3	635253000
1 - 10 mm // 1/32 - 3/8 "	3/8" - 24 UNF	33.3 mm / 1.31 "	61 mm / 2.41 "	0.17 kg / 0.37 lbs	2	635254000
1.5 - 13 mm // 1/16 - 1/2 "	3/8" - 24 UNF	42.5 mm / 1.67 "	74 mm / 2.91 "	0.31 kg / 0.68 lbs	2	635255000
1.5 - 13 mm // 1/16 - 1/2 "	1/2" - 20 UNF	42.5 mm / 1.67 "	74 mm / 2.91 "	0.32 kg / 0.71 lbs	2	635304000