

HSS-G metal drill bits long, DIN 340

- Precision spiral drill bit made of high-grade high-speed steel according to DIN 340, ground from the solid, long, cylindrical, right-hand cutting, type N, crosswise grinding 135° according to DIN 1412 C (from 3 mm), diameter tolerance h8
- Bare surface
- For highest demands and precision in industry and handcraft
- For drilling steels, cast steel, alloyed and unalloyed, grey cast iron, ductile cast iron, sintered iron, nickel silver, graphite. Up to 900 N/mm² tensile strength.



Representative picture

Diameter	Overall length	Working length	Sales unit	Order No.
2 mm	85 mm	56 mm	1	625031000
3 mm	100 mm	66 mm	1	625033000
4 mm	119 mm	78 mm	1	625038000
5 mm	132 mm	87 mm	1	625043000
6 mm	139 mm	91 mm	1	625050000
7 mm	156 mm	102 mm	1	625053000
8 mm	165 mm	109 mm	1	625055000
9 mm	175 mm	115 mm	1	625057000
10 mm	184 mm	121 mm	1	625059000

Diameter	Overall length	Working length	Sales unit	Order No.
11 mm	195 mm	128 mm	1	625062000
12 mm	205 mm	134 mm	1	625064000
13 mm	205 mm	134 mm	1	625066000