

HSS core drills, short

- With Weldon shank 19 mm (3/4")
- Insert only with suitable centring pin
- Suitable for steel, cast steel, non-ferrous metals and alloys



Representative picture

Diameter	Overall length	Working length	Order No.
12 mm	64 mm	30 mm	626500000
13 mm	64 mm	30 mm	626501000
14 mm	64 mm	30 mm	626502000
15 mm	64 mm	30 mm	626503000
16 mm	64 mm	30 mm	626504000
17 mm	64 mm	30 mm	626505000
18 mm	64 mm	30 mm	626506000
19 mm	64 mm	30 mm	626507000
20 mm	64 mm	30 mm	626508000

Diameter	Overall length	Working length	Order No.
21 mm	64 mm	30 mm	626509000
22 mm	64 mm	30 mm	626510000
23 mm	64 mm	30 mm	626511000
24 mm	64 mm	30 mm	626512000
25 mm	64 mm	30 mm	626513000
26 mm	64 mm	30 mm	626514000
27 mm	64 mm	30 mm	626515000
28 mm	64 mm	30 mm	626516000
29 mm	64 mm	30 mm	626517000
30 mm	64 mm	30 mm	626518000
31 mm	64 mm	30 mm	626519000
32 mm	64 mm	30 mm	626520000