

HSS core drills, long

- With Weldon shank 19 mm (3/4")
- Insert only with suitable centring pin
- Suitable for steel, cast steel, non-ferrous metals and alloys



Representative picture

Diameter	Overall length	Working length	Order No.
12 mm	90 mm	55 mm	626521000
13 mm	90 mm	55 mm	626522000
14 mm	90 mm	55 mm	626523000
15 mm	90 mm	55 mm	626524000
16 mm	90 mm	55 mm	626525000
17 mm	90 mm	55 mm	626526000
18 mm	90 mm	55 mm	626527000
19 mm	90 mm	55 mm	626528000
20 mm	90 mm	55 mm	626529000

Diameter	Overall length	Working length	Order No.
21 mm	90 mm	55 mm	626530000
22 mm	90 mm	55 mm	626531000
23 mm	90 mm	55 mm	626532000
24 mm	90 mm	55 mm	626533000
25 mm	90 mm	55 mm	626534000
26 mm	90 mm	55 mm	626535000
27 mm	90 mm	55 mm	626536000
28 mm	90 mm	55 mm	626537000
29 mm	90 mm	55 mm	626538000
30 mm	90 mm	55 mm	626539000
31 mm	90 mm	55 mm	626540000
32 mm	90 mm	55 mm	626541000