



Representative picture

Quality class A 36-U / A 46-U / A 60-U "Flexiarapid Super" Inox HydroResist

- The super-thin high-output disc especially for processing stainless steel
- Super quick with very long service life thanks to the use of special corundums
- Low in iron, sulphur and chlorine (Fe + S + Cl ≤ 0.1 %)
- For all rust and acid resistant steels (V2A, Nirosta, INOX), spring steels, tool steels
- For use in the manufacture of vehicles, containers, car bodies, switch cabinets etc.
- Cutting discs for quiet, precise cutting, cuts without burrs
- Hardness: hard
- Maximum working speed 80 m/s

Quality class	Diameter x thickness x bore	Version	Maximum speed	Sales unit / packaging unit	Order No.
A 60-U	115 x 0.8 x 22.23 mm	offset	13300 rpm	1 / 50	616208000
A 60-U	125 x 0.8 x 22.23 mm	offset	12200 rpm	1 / 50	616209000
A 60-U	105 x 1 x 16 mm	straight	15300 rpm	1 / 25	616210000
A 60-U	115 x 1 x 22.23 mm	straight	13300 rpm	1 / 25	616216000
A 60-U	115 x 1 x 22.23 mm	offset	13300 rpm	1 / 25	616217000
A 46-U	115 x 1.6 x 22.23 mm	straight	13300 rpm	1 / 25	616218000

Quality class	Diameter x thickness x bore	Version	Maximum speed	Sales unit / packaging unit	Order No.
A 46-U	115 x 1.6 x 22.23 mm	offset	13300 rpm	1 / 25	616219000
A 60-U	125 x 1 x 22.23 mm	straight	12200 rpm	1 / 25	616220000
A 46-U	125 x 1.6 x 22.23 mm	straight	12200 rpm	1 / 25	616222000
A 46-U	150 x 1.6 x 22.23 mm	straight	10200 rpm	1 / 25	616224000
A 36-U	180 x 1.6 x 22.23 mm	straight	8500 rpm	1 / 25	616226000
A 36-U	180 x 1.6 x 22.23 mm	offset	8500 rpm	1 / 25	616227000
A 36-U	230 x 1.9 x 22.23 mm	straight	6600 rpm	1 / 25	616228000
A 36-U	230 x 1.9 x 22.23 mm	offset	6600 rpm	1 / 25	616229000
A 60-U	115 x 1.2 x 22.23 mm	straight	13300 rpm	1 / 25	616233000
A 60-U	125 x 1.2 x 22.23 mm	straight	12200 rpm	1 / 25	616234000
A 60-U	105 x 1 x 16 mm	straight	15300 rpm	50 / 1	616347000