



Representative picture

Quality class zirconia alumina "Flexiamant Convex"

- Specially shaped flap disc with lamellae that are rounded off towards the outer edges.
- Grinding media: Zirconia alumina
- Thanks to the special design it is particularly suited for processing fillet welds; making faster and more efficient processing possible; also suitable for surface grinding
- High material removal with very high tool life thanks to the use of zirconia alumina
- Suitable for processing stainless steel and steel
- Uniform grinding result, comfortable grinding with only low vibration
- Maximum working speed 80 m/s

Diameter x bore	Grit	Version	Maximum speed	Sales unit / packaging unit	Order No.
125 x 22.23 mm // 5 x 7/8 "	P 40	offset	12200 rpm	1 / 10	626462000
125 x 22.23 mm // 5 x 7/8 "	P 60	offset	12200 rpm	1 / 10	626463000
125 x 22.23 mm // 5 x 7/8 "	P 80	offset	12200 rpm	1 / 10	626464000
150 x 22.23 mm // 6 x 7/8 "	P 40	offset	10200 rpm	1 / 10	626490000
150 x 22.23 mm // 6 x 7/8 "	P 60	offset	10200 rpm	1 / 10	626491000

Diameter x bore	Grit	Version	Maximum speed	Sales unit / packaging unit	Order No.
150 x 22.23 mm // 6 x 7/8 "	P 80	offset	10200 rpm	1 / 10	626492000