



Representative picture

Quality class ceramic "Flexiamant Super Convex"

- Specially shaped flap disc with lamellae that are rounded off towards the outer edges.
- Thanks to the special design it is particularly suited for processing fillet welds; making faster and more efficient processing possible; also suitable for surface grinding
- Very high material removal with very high tool life thanks to the use of ceramic grain.
- Cool cut for materials with poor thermal conduction
- For grinding of steel and stainless steel. Ideal for extreme grinding jobs like processing high-alloy steels, titanium alloys, nickel-based alloys as well as chromium and chromium-nickel steels, brass and bronze thanks to high load capacity.
- Uniform grinding result, comfortable grinding with only low vibration
- Maximum working speed 80 m/s

Diameter x bore	Grit	Version	Maximum speed	Sales unit / packaging unit	Order No.
125 x 22.23 mm // 5 x 7/8 "	P 60	offset	12200 rpm	1 / 10	626460000
125 x 22.23 mm // 5 x 7/8 "	P 80	offset	12200 rpm	1 / 10	626461000
150 x 22.23 mm // 6 x 7/8 "	P 60	offset	10200 rpm	1 / 10	626488000
150 x 22.23 mm // 6 x 7/8 "	P 80	offset	10200 rpm	1 / 10	626489000